SPECIFICATIONS FOR SINGLE BOILERLESS GAS COMBI OVEN

Oven shall be model **BX-14G** as manufactured by the Combi Division of Blodgett Oven Corporation. Combi-Oven/Steamer shall have all the following standard and accessory features:

EXTERIOR CONSTRUCTION

Stainless steel top, front and sides

Dual pane tempered viewing window with hinged inner glass for easy

cleaning

Door mounted condensate trough

Top and bottom mount, easily adjustable door hinges

Pivot out user interface panel for service access

INTERIOR CONSTRUCTION

Fully welded stainless steel frame

Fully insulated cooking chamber

Fixed drain bottom center of cavity

Easily removable stainless steel side rails

316 stainless steel coved corner liner for ease of cleaning

OPERATION

Standard control with function selection for steam, combi, hot air and cool

down

Retherm band on control

Steam on demand feature

Thermostat control to 500F

Multiple speed reversing fan for even bake

Dual stage door latch to vent steam before fully opening door

Cavity vent control provides ability to release steam at the turn of a switch

Integral door switch

Electronic spark ignition

Open vented system. Condenses steam and drains away by-products of the cooking process, eliminates flavor transfer

CAPACITY

Fourteen 12" x 20" x 2-1/2" deep pans at 3-1/4" spacing

Seven 18" x 26" deep pans at 3-1/4" spacing

STANDARD FEATURES

Five (5) stainless steel wire shelves per section (capacity for 7)

Hinged pressure panel for cleanability

Four halogen lights for superior cavity illumination

Retractable hose reel hidden behind door, no extraneous hoses

Stacking kit and casters for double stack ovens

Pressure spray bottle for oven cleaning

6-1/2" core temperature probe

Start-up inspection service by factory authorized service agent

One year parts and labor oven warranty*

REQUIRED ACCESSORIES

ACS-22-8 22" high stand with universal pan slides

OPTIONAL ACCESSORIES

Limited Extended Warranty (one extra year maximum, for total of 2 years.)

Blodgett - Combi Fry Pan

Extra oven racks

SMFS2 Terry Water Treatment System for Scale & Corrosion Control

- ELIGIBLE BIDDER MUST VISIT JOB SITE.
- ALTERNATES NEED TO BE SUBMITTED FOR APPROVAL 10 DAYS PRIOR TO BID OPENING.
- SUCCESSFUL BIDDER TO DELIVER, UNCRATE, SET IN PLACE, LEVEL, AND REMOVE CRATING.
- FINAL CONNECTIONS BY OTHERS
- BIDDER WILL HONOR PRICES FOR A PERIOD OF ONE YEAR FROM THE BID DATE____yes____no.
- BIDDER WILL HONOR PRICING FOR COOPERATIVE PRICING____yes___no.

(Additional travel/mileage charges may apply to systems that are located outside the bidding system's area)