SPECIFICATION FOR 6, 10 OR 12 GALLON ELECTRIC TABLE TOP TILT KETTLE

Tilt kettle shall be model KTT-6E (6 gallon)/KTT-10E (10 gallon)/KTT-12E (12 gallon) kettle as manufactured by Blodgett. The kettle shall have all the following standard and accessory features:

CONSTRUCTION

Water resistant construction

304 stainless steel construction

316 stainless steel interior cooking surface for added corrosion

resistance

2/3 jacketed with factory sealed distilled water enclosure

Hemispherical design on bottom of kettle for superior heat circulation

Stainless steel control housing

Concealed mounting lugs for bolting unit to counter top

OPERATION

Electrically self-generated closed steam system

Integrally mounted controls

Power switch

Thermostat

Cook indicator light

Pressure gauge

Safety valve

Low water light

Low water shut off

165-285°F (75-140°C) temperature range

STANDARD FEATURES

Removable elements

Removable operating handle with heat proof knob

"Clean Lock" holds kettle in cooking position or 105° for ease of cleaning

Manual control

Mounts to countertop (optional stand available)

Stainless steel faucet bracket

Voltage to be determined_____

One year parts and labor warranty*

OPTIONAL ACCESSORIES

Single pantry faucet with swing spout

Double pantry faucet with swing spout

Etched markings/Gallons

18" (46 mm) high stainless steel stand with sliding drawer and stationary drain

One piece stainless steel lift off cover

Stainless steel perforated basket

Pour strainer

- · ELIGIBLE BIDDER MUST VISIT JOB SITE.
- ALTERNATES NEED TO BE SUBMITTED FOR APPROVAL 10 DAYS PRIOR TO BID OPENING.
- SUCCESSFUL BIDDER TO DELIVER, UNCRATE, SET IN PLACE, LEVEL, AND REMOVE CRATING.
- FINAL CONNECTIONS BY OTHERS
- BIDDER WILL HONOR PRICES FOR A PERIOD OF ONE YEAR FROM THE BID DATE____yes____no.
- BIDDER WILL HONOR PRICING FOR COOPERATIVE PRICING____yes____no.
 (Additional travel/mileage charges may apply to systems that are located outside the bidding system's area)